



INSULATED END SEALING FERRULES



MATERIAL : ELECTROLYTIC COPPER BS 1977 / IS 191 (PART V)
FINISH : ELECTRO TINNED

MM ²	COLOUR	J2	øA	øC	D	F	J1	CAT NO.
0.5	WHITE	6	1.1	1.5	2.6	0.5	12	KK-0.5/6
0.5	WHITE	8	1.1	1.5	2.6	0.5	14	KK-0.5/8
0.5	WHITE	10	1.1	1.5	2.6	0.5	16	KK-0.5/10
0.75	BLUE	8	1.5	1.9	2.8	0.5	14	KK-0.75/8
0.75	BLUE	10	1.5	1.9	2.8	0.5	16	KK-0.75/10
1.0	RED	8	1.7	2.1	3.3	0.5	14	KK-1.0/8
1.0	RED	10	1.7	2.1	3.3	0.5	16	KK-1.0/10
1.0	RED	12	1.7	2.1	3.3	0.5	18	KK-1.0/12
1.5	BLACK	8	1.9	2.3	3.5	0.5	14	KK-1.5/8
1.5	BLACK	10	1.9	2.3	3.5	0.5	16	KK-1.5/10
2.5	BLUE	8	2.4	2.8	4.2	0.5	14	KK-2.5/8
2.5	BLUE	12	2.4	2.8	4.2	0.5	18	KK-2.5/12
4	GREY	10	2.9	3.3	4.8	0.5	16	KK-4/10
4	GREY	12	2.9	3.3	4.8	0.5	18	KK-4/12
6	GREEN	10	3.8	4.2	6.3	0.5	18	KK-6/10
6	GREEN	12	3.8	4.2	6.3	0.5	20	KK-6/12
6	GREEN	15	3.8	4.2	6.3	0.5	23	KK-6/15
10	BROWN	15	4.7	5.1	7.6	0.7	25	KK-10/15
10	BROWN	18	4.7	5.1	7.6	0.7	28	KK-10/18
16	WHITE	12	6.0	6.4	8.8	0.7	24	KK-16/12
16	WHITE	15	6.0	6.4	8.8	0.7	27	KK-16/15
25	YELLOW	22	7.3	7.7		0.7		KK-25/22
35	BLUE	25	8.3	8.7		0.7		KK-35/25
50	BLUE	25	10.3	10.7		0.7		KK-50/25

BIGGER SIZE CAN BE MANUFACTURED AGAINST SPECIFIC REQUIREMENT AND IN REQUIRED COLOURS.
 THE END SEALING FERRULES / BOOTLACE PINS ARE SUITABLE TO USE IN TERMINAL BLOCKS AND CAPTIVE TERMINALS.